



TC51 / TC56

Ghid accesorii

Baterii / Accesorii de încărcare a bateriilor

Baterie 4300mAh

BTRY-TC51-43MA1-01

Baterie suplimentară Li-Ion PowerPrecision+ 4300 mAh. Tehnologie avansată, oferă un nivel mai înalt de inteligență (stare încărcare și stare sănătate) pentru a oferi performanțe maxime (1 bucată).



Disponibil și în pachet de 10 baterii (PN: BTRY-TC51-43MA1-10)

Indicator LED

Stins	Bateria nu se încarc
ortocaliu aprins	nc rcare corect baterie
erde aprins	nc rcare corect baterie terminat
o u clipind rapid	nc rcare corect baterie terminat
o u aprins	nc rcare baterie incorect sau inc rcare complet

Opțiuni de încărcare baterii suplimentare:

SAC-TC51-4SCHG-01

Încărcător 4 baterii TC51/56, încarcă patru baterii suplimentare. Include: sursă alimentare PWR- BGA12V50W0WW și cablu alimentare CBL-DC-388A1-01. Cablu AC specific țării, cadru perete/raft vândut separat.



Sursă de alimentare și cablu DC inclus pentru încărcător baterii:

Sursă alimentare pentru 4 baterii încărcător: 100-240 VAC, 12VDC, 4.16A. (PN: PWR-BGA12V50W0WW)
Necesită: Cablu AC cu ștecher EU.



Cablu DC pentru sursă alimentare nivel 6 PWR- BGA12V50W0WW (12 VDC, 4.16A), 1,8 M lungime. (PN: CBL-DC-388A1-01)

Cablu AC EU



50-16000-220R
Cablu AC alimentare EU, 1,8m lungime, împământare, trei fire

Charging Options

Single Slot Cradle



ShareCradle, Charge & USB Communication

CRD-TC51-1SCU-01: TC51/56 Single Slot Charge/USB ShareCradle. Charges and allows USB communication to one device. Includes PWR-BGA12V50W0WW and DC cable CBL-DC-388A1-01. Country Specific AC Line Cord and 25-124330-01R Micro-USB Cable, Sold Separately.

KT-TC51-ETH1-01: USB-Ethernet Adapter kit for ShareCradle single-slot. Includes housing to secure Ethernet module to cradle.

Included with single-slot cradle



Power supply for single-slot cradle:
100-240 VAC, 12VDC, 4.16A.
(PN: PWR-BGA12V50W0WW)
Requires: Country specific AC grounded line cord.

DC cable for power supply
PWR-BGA12V50W0WW. (12 VDC, 4.16A) 1.8m length.
(PN: CBL-DC-388A1-01)

Additional accessories for single slot cradle



23844-00-00R

US AC line cord, 7.5 feet long, grounded, three wire for power supplies.



25-124330-01R

Micro-USB to USB Cable for single slot cradle communication.

Note: Spare cradle cups are available as service spare parts.

Charging Options

Multi-Slot Cradles



Cradle options:

CRD-TC51-5SCHG-01: TC51/56 5-Slot Charge Only Cradle, charges up to five devices. Includes power supply PWR-BGA12V108W0WW and DC cable CBL-DC-382A1-01. Country specific AC line cord sold separately.

CRD-TC51-5SETH-01: TC51/56 5-Slot Ethernet Cradle, charges up to five devices and provides Ethernet communication. Includes power supply PWR-BGA12V108W0WW and DC cable CBL-DC-382A1-01. Country specific AC line cord sold separately.

CRD-TC51-5SC4B-01: TC51/56 5-Slot Charge Only Cradle with 4-Slot Spare Battery Charger, charges up to 4 devices and up to 4 spare batteries. Includes power supply PWR-BGA12V108W0WW and DC cable CBL-DC-382A1-01. Country specific AC line cord sold separately.

Included with multi-slot cradles



Power supply for multi-slot cradle:
100-240 VAC, 12VDC, 9A.
(PN: PWR-BGA12V108W0WW)

Requires: Country specific AC grounded line cord.



DC cable provides power from the power supply to multi-slot charge-only and Ethernet cradles.
(PN: CBL-DC-382A1-01)

Additional accessories for multi-slot cradle



23844-00-00R

US AC line cord, 7.5 feet long, grounded, three wire for power supplies.

Note: Spare cradle cups are available as service spare parts.

Charging Options

Mount options for multi-slot cradles



MAXIMUM DENSITY

RACK MOUNTED SOLUTION:

The Rack/Wall Mount Bracket have been optimized to work on a standard 19-inch rack, maximized density. The brackets can also be configured in different angles for maximum flexibility.



Rack/Wall bracket for multi-slot cradle



BRKT-SCRD-SMRK-01

Rack/Wall mounting bracket, allows to install any Single-Slot or Multi-Slot cradle on a wall or a 19" IT rack. The bracket also allows to install up to four 4-Slot Spare Battery Chargers together on a wall or standard 19" IT rack.

Compatible with all multi-slot cradle options:

CRD-TC51-5SCHG-01: 5-Slot Charge Only Cradle, charges up to five devices. (Includes Power supply and DC cable)

CRD-TC51-5SETH-01: 5-Slot Ethernet Cradle, charges up to five devices and provides Ethernet communication. (Includes Power supply and DC cable)

CRD-TC51-5SC4B-01: 4-Slot Charge Only Cradle with 4-Slot Spare Battery Charger, charges up to 4 devices and up to 4 spare batteries on the same cradle. (Includes Power supply and DC cable)

SAC-TC51-4SCHG-01: TC51/56 4-slot battery charger, charges four spare batteries. (Includes Power supply and DC cable)

Upgrade to Rugged Boot or Trigger Handle Configurations

Rugged Boot

SG-TC51-EXO1-01

TC51/56 Rugged Boot and Handstrap. Provides additional protection to the device and allows user to attach a trigger handle.



Trigger Handle

KT-TC51-TRG1-01

TC51/56 Snap-On Trigger Handle and Rugged Boot Kit. Trigger handle easily attaches to rugged boot and easily removed to access battery. Trigger handle includes a tether point for a wrist tether. Wrist Tether (SG-PD40-WLD1-01) sold separately.



TRG-TC51-SNP1-01

TC51/56 Snap-On Trigger Handle. Requires TC51/56 rugged boot (sold separately or included in above kit KT-TC51-TRG1-01). Wrist Tether and rugged boot sold separately.



Soft-Goods Accessories

Hand Strap



SG-TC51-EHDSTP1-03

TC51/56 Replacement Handstrap for devices configured with a rugged boot (3-pack). Provides added safety against accidental drops of the device while on the move.

Basic Hand Strap Kit



SG-TC51-BHDSTP1-03

TC51 Basic Handstrap kit. Allows TC51 devices without a rugged boot to be configured with a handstrap (3-pack). For use with TC51 WLAN configurations only.

Soft Holster

SG-TC51-HLSTR1-01

TC51/56 soft holster for vertical orientation with open bucket design for easy insertion and removal. Features adjustable straps to accommodate handstrap, rugged boot and trigger handle configurations.



Stylus

SG-TC7X-STYLUS-03

Stylus with coiled tether 3-Pk. Made of conductive carbon-filled plastic material, optimized for enterprise durability.



Cables / Adapters

Rugged Charge Cable

CBL-TC51-USB1-01

TC51/56 Rugged USB/Charge Cable.
Accommodates TC51/56 with and without rugged boot.



Wall Charger – Power Supply

PWR-WUA5V12W0XX

Power Supply-100-240 VAC, 5 V,
2.5 A with country specific plugs.



Country	Power Supply Part Number
United States	PWR-WUA5V12W0US
Great Britain	PWR-WUA5V12W0GB
Europe	PWR-WUA5V12W0EU
Australia	PWR-WUA5V12W0AU
China	PWR-WUA5V12W0CN
Brazil	PWR-WUA5V12W0BR
Korea	PWR-WUA5V12W0KR
India	PWR-WUA5V12W0IN

Audio Cables

CBL-TC51-HDST25-01

2.5MM Female to 3.5MM Male
Headset Adapter Cable.



CBL-TC51-HDST35-01

3.5MM Collared Female to 3.5MM
Male Headset Adapter Cable.

HSDT-35MM-PTVP-01

Over the ear headset
with/MIC and PTT-3.5mm.
Requires 3.5MM adapter
cable CBL-TC51-HDST35-
01 (sold separately).



Country Specific AC Line Cord Options

Country	Three Wire AC Line Cord
Abu Dhabi	50-16000-220R: 1.8M long, CEE 7/7 plug.
Australia	50-16000-217R: 1.9M long, AS 3112 plug.
Bolivia	50-16000-220R: 1.8M long, CEE 7/7 plug.
Brazil	50-16000-727R: 18AWG, 250V, 16A, BR (3w).
China	50-16000-217R: 1.9M long, AS 3112 plug. 50-16000-257R: 1.8M long, IEC 60320 C13 plug.
Dubai	50-16000-220R: 1.8M long, CEE 7/7 plug.
Egypt	50-16000-220R: 1.8M long, CEE 7/7 plug.
Europe	50-16000-220R: 1.8M long, CEE 7/7 plug.
Hong Kong	50-16000-219R: 1.8M long, BS1363 plug.
India	50-16000-669R: 1.9M long, BS 546 plug.
Iran	50-16000-220R: 1.8M long, CEE 7/7 plug.
Iraq	50-16000-219R: 1.8M long, BS1363 plug.

Country	Three Wire AC Line Cord
Israel	50-16000-672R: 1.9M long, S132 plug.
Italy	50-16000-671R: 1.8M long, CIE 23-16 plug.
Japan	50-16000-218R: 1.8M long, NEMA 1-15P plug.
Korea	50-16000-220R: 1.8M long, CEE 7/7 plug. 50-16000-256R: 1.8M long, CEE7/7 plug.
Malaysia	50-16000-219R: 1.8M long, BS1363 plug.
New Guinea	50-16000-217R: 1.9M long, AS 3112 plug.
Russia	50-16000-220R: 1.8M long, CEE 7/7 plug.
Singapore	50-16000-219R: 1.8M long, BS1363 plug.
UK	50-16000-219R: 1.8M long, BS1363 plug.
US	23844-00-00R: 7.5 feet long. 50-16000-221R: 1.8M long, USA NEMA 5-15P.
Vietnam	50-16000-220R: 1.8M long, CEE 7/7 plug.